Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-344-4906

	ional Shape:
Emi	
Hole Diame	eter:
	115 inches and 0.135 inches
Overall Ler	ngth:
Between 1.	110 inches and 1.140 inches
Overall Wid	ith:
Between 1.	110 inches and 1.140 inches
Aperture D	iameter:
Between 0.9	938 inches and 0.958 inches
Outside Co	orner Radius:
0.109 inche	S
Center To	Center Distance Between Bolt Holes Along Width:
Between 0.8	396 inches and 0.916 inches
Center To	Center Distance Between Bolt Holes Along Length:
Between 0.8	396 inches and 0.916 inches
Cross-sect	ional Height:
Between 0.0	D27 inches and 0.037 inches
Bolt Hole G	Quantity:
4	
Environme	ntal Protection Material Location:
Throughout	rf shielding gasket
Material:	
Copper emi	/rfi conductorrubber silicone class q environmental seal
	laterial And Location:
Emi/rfi cond	luctive particle surfaces silver
Precious M	
Silver	
Surface Tre	eatment:
Silver emi/rl	
Style Desig	
Non-circula	
Test Data	
	-83528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
-	ludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	tal and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specificatio	
-	
Shelf Life:	-83528/4 government specification
N/a	
Unit Of Mea	asure:
Demilitariz	ation:
No	

## NSN 5999-01-344-4906

Electronic Shielding Gasket - Page 2 of 2

**Fiig:** A032a0

