NSN 5999-01-346-0672



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-346-0672 **Body Style:** Rectangular **Body Length:** 0.780 inches **Body Width:** 0.280 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 14 **Voltage Rating:** Between 4.750 volts and 5.250 volts **Material And Location:** Plastic, silicone, mil-m-14, type msg body err-100 err-100 nickel, qq-n-281, class a terminal err-100 err-100 and iron alloy terminal err-100 err-100 **Surface Treatment And Location:** Tin plated terminal err-100 err-100 **Body Depth:** 0.290 inches **Mounting Facility: Terminal Signal Delay Method:** Solid state **Delay Time Variation Method: Tapped Section Delay Time:** 100.000 nanoseconds single section **Segment Quantity Per Section:** 10 single section **Segment Delay Time:** 8.000 nanoseconds single section all segments and 12.000 nanoseconds single section all segments **Pulse Rise Time Rating:** 2.0 microseconds **Terminal Type And Quantity:** 14 pin

Shelf Life: N/a

Special Features:

Electrostatic sensitive device

NSN 5999-01-346-0672

Delay Line - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100