

View Online at <https://aerobasegroup.com/nsn/5999-01-346-9603>

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.125 inches and 0.145 inches

Overall Length:

Between 1.138 inches and 1.168 inches

Overall Width:

Between 1.138 inches and 1.168 inches

Aperture Diameter:

Between 1.005 inches and 1.025 inches

Outside Corner Radius:

0.175 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.896 inches and 0.916 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.896 inches and 0.916 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.124 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.124 inches

Cross-sectional Height:

Between 0.027 inches and 0.037 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Material:

Aluminum emi/rfi conductor/rubber fluorosilicone class fq environmental seal

Precious Material And Location:

Emi/rfi conductive particles silver

Precious Material:

Silver

Surface Treatment:

Silver emi/rfi conductor

Style Designator:

Non-circular

Test Data Document:

81349-mil-g-83528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-g-83528/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0