

View Online at <https://aerobasegroup.com/nsn/5999-01-351-2880>

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.162 inches and 0.182 inches

Overall Length:

Between 1.610 inches and 1.640 inches

Overall Width:

Between 1.610 inches and 1.640 inches

Aperture Diameter:

Between 1.375 inches and 1.395 inches

Outside Corner Radius:

0.265 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.240 inches and 1.260 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.240 inches and 1.260 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.185 inches and 0.190 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.185 inches and 0.190 inches

Cross-sectional Height:

Between 0.027 inches and 0.037 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Material:

Aluminum alloy emi/rfi conductorrubber silicone class q environmental seal

Precious Material And Location:

Emi/rfi conductive particles silver

Precious Material:

Silver

Surface Treatment:

Silver emi/rfi conductor

Style Designator:

Non-circular

Test Data Document:

81349-mil-g-83528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-g-83528/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0