## NSN 5999-01-351-7240

Delay Line - Page 1 of 2



7240

View Online at https://aerobasegroup.com/nsn/5999-01-351-7
Body Style:
Rectangular
Body Length:
0.810 inches
Body Width:
0.510 inches
Individual Section Quantity:
1
Longest Vertical Distance Between Mounting Centers:
Between 0.290 inches and 0.310 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
8
Voltage Rating:
Between 4.500 volts and 5.500 volts
Material And Location:
Plastic, mil-m-14, type sdg-f case or plastic, epoxy case
Body Depth:
0.165 inches
Mounting Facility:
Pin
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
75.000 nanoseconds single section
Segment Quantity Per Section:
5 single section
Segment Delay Time:
15.000 nanoseconds single section all segments
Pulse Rise Time Rating:
4.0 nanoseconds
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 5999-01-351-7240

Delay Line - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A32100

