

View Online at <https://aerobasegroup.com/nsn/5999-01-352-0922>

**Cross Sectional Shape:**

Metal and synthetic rubber

**Hole Diameter:**

0.112 inches

**Overall Length:**

1.438 inches

**Overall Width:**

1.438 inches

**Aperture Width:**

Between 0.1105 inches and 0.1135 inches

**Aperture Length:**

Between 0.2225 inches and 0.2255 inches

**Outside Corner Bevel Length Along Width:**

0.060 inches

**Outside Corner Bevel Length Along Length:**

0.060 inches

**Center To Center Distance Between Bolt Holes Along Width:**

1.125 inches

**Center To Center Distance Between Bolt Holes Along Length:**

1.125 inches

**Cross-sectional Thickness:**

Between 0.185 inches and 0.187 inches

**Gage Ring Thickness:**

Between 0.185 inches and 0.187 inches

**Bolt Hole Quantity:**

4

**Environmental Protection Material Location:**

Around rf shielding gasket aperture

**Special Features:**

Two alignment pins spaced 0.656 in. C to c; mtg holes are threaded 40-unc-2b; four unthreaded holes spaced 0.530 in. By 0.500 in.

**Material:**

Copper alloy emi/rfi conductor silicone environmental seal

**Material Specification:**

Mil-f-3922 military specification single material response emi/rfi conductor z-z-r-765, class 2a, grade 60 federal specification single material response environmental seal

**Precious Material And Location:**

Gasket surfaces gold

**Precious Material:**

Gold

**Surface Treatment:**

Gold emi/rfi conductor

**Surface Treatment Specification:**

Mil-f-14072, -310 military specification single treatment response emi/rfi conductor

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-f-3922 spec.