

View Online at <https://aerobasegroup.com/nsn/5999-01-352-3544>

Body Style:

Rectangular, front connection

Overall Depth:

0.410 inches

Body Length:

0.800 inches

Body Width:

0.400 inches

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

8

Voltage Rating:

Between 4.750 volts and 5.250 volts

Material And Location:

Plastic, diallyl phthalate, mil-m-14, type sdi-30 case err-100 err-100 or plastic, epoxy case err-100 err-100 nickel-copper alloy, qq-n-281, class a terminal err-100 err-100

Surface Treatment And Location:

Tin plated, mil-t-10727, type 1 terminal

Body Depth:

0.260 inches

Mounting Facility:

Terminal

Signal Delay Method:

Solid state

Delay Time Variation Method:

Tapped

Section Delay Time:

300.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

60.000 nanoseconds single section all segments

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100