

View Online at <https://aerobasegroup.com/nsn/5999-01-352-7056>

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

0.800 inches

Body Width:

0.400 inches

Individual Section Quantity:

1

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

8

Voltage Rating:

Between 4.750 volts and 5.250 volts

Material And Location:

Plastic, epoxy case err-100 err-100 or plastic, mil-m-14, type sgd-f case err-100 err-100 nickel-copper alloy, qq-n-281, class a terminal err-100 err-100

Surface Treatment And Location:

Tin plate, mil-t-10727, type 1 or 2 terminal

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.260 inches

Mounting Facility:

Pin

Attenuation In Decibels:

Not rated

Signal Delay Method:

Solid state

Delay Time Variation Method:

Tapped

Section Delay Time:

250.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

50.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100