Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-354-9739

| ross Sectional Shape: |
|---|
| mi |
| ole Diameter: |
| etween 0.253 inches and 0.262 inches |
| verall Length: |
| .880 inches |
| empurature Rating: |
| 03.0 degrees celsius and 401.0 degrees celsius |
| verall Width: |
| .630 inches |
| perture Width: |
| .370 inches |
| perture Length: |
| .620 inches |
| enter To Center Distance Between Bolt Holes Along Width: |
| .667 inches |
| enter To Center Distance Between Bolt Holes Along Length: |
| .312 inches |
| outside Edge To Bolt Hole Center Distance Along Width: |
| .312 inches |
| outside Edge To Bolt Hole Center Distance Along Length: |
| .312 inches |
| ross-sectional Height: |
| etween 0.109 inches and 0.157 inches |
| olt Hole Quantity: |
| 4 |
| • nvironmental Protection Material Location: |
| hroughout rf shielding gasket |
| utside Edge To Inside Edge Smallest Distance Along Width: |
| .630 inches |
| utside Edge To Inside Edge Smallest Distance Along Length: |
| .630 inches |
| laterial: |
| dhesive backingnickel alloy 400 emi/rfi conductorrubber silicone class q environmental seal |
| laterial Specification: |
| Iq-n-281 federal specification single material response emi/rfi conductorams-3195 national specification single material respor |
| |
| |
| tyle Designator: on-circular |
| helf Life: |
| |
| /a nit Of Monsure: |
| nit Of Measure: |
| |

NSN 5999-01-354-9739

Electronic Shielding Gasket - Page 2 of 2

Demilitarization:

No

Fiig:

A032a0

