

View Online at <https://aerobasegroup.com/nsn/5999-01-383-0556>

**Overall Length:**

Between 0.450 inches and 0.470 inches

**Overall Height:**

Between 0.040 inches and 0.050 inches

**Overall Width:**

Between 0.024 inches and 0.026 inches

**Pin Length:**

Between 0.410 inches and 0.430 inches

**Mounting Method:**

Force fit

**Special Features:**

No plating on contact tip materials: beryllium copper per astm b194, cond 1/4 hard, alloy 172 or phosphor bronze per astm b139 composition a (alloy cda 510, grade a hard drawn.

**Material:**

Copper alloy body and contact

**Precious Material And Location:**

All surfaces except the tip. Gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Surface Treatment:**

Gold body and contact and nickel body and contact

**Surface Treatment Specification:**

Mil-g-45204type ii grade c military specification 1st treatment response body and contact and qq-n-290 class 2 except thickness federal specification 2nd treatment response body and contact

**Style Designator:**

Post contact

**Test Data Document:**

13499-372-2601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A222a0

**Mil-std (military Standard):**

Mil-g-45204type spec.