NSN 5999-01-383-0556

Electrical Contact - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-383-0556 **Overall Length:** Between 0.450 inches and 0.470 inches **Overall Height:** Between 0.040 inches and 0.050 inches Overall Width: Between 0.024 inches and 0.026 inches Pin Length: Between 0.410 inches and 0.430 inches **Mounting Method:** Force fit **Special Features:** No plating on contact tip materials: beryllium copper per astm b194, cond 1/4 hard, alloy 172 or phosphor bronze per astm b139 composition a (alloy cda 510, grade a hard drawn. Material: Copper alloy body and contact **Precious Material And Location:** All surfaces except the tip. Gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Surface Treatment:** Gold body and contact and nickel body and contact **Surface Treatment Specification:** Mil-g-45204type ii grade c military specification 1st treatment response body and contact and qq-n-290 class 2 except thickness federal

specification 2nd treatment response body and contact

Style Designator:

Post contact

Test Data Document:

13499-372-2601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A222a0

Mil-std (military Standard):

Mil-g-45204type spec.