

View Online at <https://aerobasegroup.com/nsn/5999-01-384-4988>

Overall Length:

Between 0.435 inches and 0.465 inches

Overall Height:

0.095 inches

Overall Width:

0.100 inches

Distance Between Mounting Facility Centers:

0.100 inches

Pin Accommodation Diameter:

Between 0.037 inches and 0.043 inches

Pin Length:

Between 0.415 inches and 0.465 inches

Pin Width:

0.095 inches

Mounting Method:

Force fit

Special Features:

Current rating : 3 to 5 amps. Temp. Range is -40 deg. C. To 105 deg. C. Dielectric with standing voltage is 1,000 volts rms insulation resistance is 5000 megohms.P

Material:

Nylon barrel insulation

Material Specification:

Qq-750 federal specification 1st material response contact

Precious Material And Location:

Body and contact gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Tin contact and nickel contact

Surface Treatment Specification:

Mil-p-81728 military specification 1st treatment response contact and qq-n-290 federal specification 2nd treatment response contact

Style Designator:

Post contact

Test Data Document:

14933-86101 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 pin end opposite contact

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A222a0

Mil-std (military Standard):

Mil-p-81728 spec.