

View Online at <https://aerobasegroup.com/nsn/5999-01-386-3987>

Body Style:

Rectangular

Body Length:

0.810 inches

Body Width:

0.400 inches

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

14

Voltage Rating:

Between 0.500 volts and 2.500 volts

Body Depth:

0.245 inches

Mounting Facility:

Terminal

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

50.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

10.000 nanoseconds single section all segments

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

14 pin

Test Data Document:

Mil-d-83532 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

Mil-d-83532/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100

Mil-std (military Standard):

Mil-d-83532 spec.