

View Online at <https://aerobasegroup.com/nsn/5999-01-386-3987>

**Body Style:**

Rectangular

**Body Length:**

0.810 inches

**Body Width:**

0.400 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Mounting Facility Quantity:**

14

**Voltage Rating:**

Between 0.500 volts and 2.500 volts

**Body Depth:**

0.245 inches

**Mounting Facility:**

Terminal

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

50.000 nanoseconds single section

**Segment Quantity Per Section:**

5 single section

**Segment Delay Time:**

10.000 nanoseconds single section all segments

**Pulse Rise Time Rating:**

4.0 nanoseconds

**Terminal Type And Quantity:**

14 pin

**Test Data Document:**

Mil-d-83532 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

Mil-d-83532/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100

**Mil-std (military Standard):**

Mil-d-83532 spec.