Electronic Shielding Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-481-1914

Cro	ss Sectional Shape:
Emi	
Hol	e Diameter:
0.15	54 inches
Ove	erall Length:
Betv	ween 47.25 millimeters and 48.01 millimeters
Ove	erall Width:
Bet	ween 47.25 millimeters and 48.01 millimeters
Аре	erture Diameter:
Betv	ween 41.28 millimeters and 41.79 millimeters
Out	side Corner Radius:
0.15	54 inches
Cer	ter To Center Distance Between Bolt Holes Along Width:
1.37	75 inches
Cen	ter To Center Distance Between Bolt Holes Along Length:
1.37	75 inches
Cro	ss-sectional Height:
0.02	20 millimeters
Bol	t Hole Quantity:
4	
End	Application:
Sup	port of pre-provisioning items for which navicp-phil acts as poe
Crit	icality Code Justification:
Aga	v
Env	vironmental Protection Material Location:
Thro	oughout rf shielding gasket
Pro	duct Name:
Gas	sket-flange, electrical connector
Mat	erial:
Rub	ber silicone class q environmental seal
	erial Specification:
Ams	s 4182 assn standard single material response emi/rfi conductor
	le Designator:
Non	n-circular
She	elf Life:
N/a	
Uni	t Of Measure:
Den	nilitarization:
No	
Fiig	:
-	2a0