

View Online at <https://aerobasegroup.com/nsn/5999-01-485-7553>

Overall Length:

Between 0.179 inches and 0.182 inches

Overall Diameter:

0.855 inches

Cable Entrance Diameter:

Between 0.098 inches and 0.102 inches

End Application:

Rka16 11447-10035205-501 contr/proc/gr; rk/a15 11447 10035204-503 msg proc gp; rka15 11447-10035204-501 msg prcs gp ; rk a22 49671 8375708-507 rev 5.3 trident; items with nuclear applications; t-1393b/slq-3 (v), xmtr, cm; an/slq-32b(v)2, miscellaneous; an/slq-32b(v)1 miscellaneous; 5849101g1(94117), lb df unit; 5849104g1(94117), vhf/uhf df unit; 5849112g1(94117), profiler group; or-358/srs-1, receiver group; an/slq-32(v)4 miscellaneous; an/slq-32(v)5 miscellaneous; an/slq-32a(v)1, 2, 3 miscellaneous (improved); an/sps-40e, radar set ; pwr cont and distance pnlpn70d184610-1001; mk15mod26, , 27, 28, 31 weapon system, close-in; mk15 mod5 11-14&21-25, ciws, i-level; mk15 mods 11-14&21-25, ciws, depot level; mk15mod21, 22, 25 weapon system, close-in; mk556 mod2 cable test set; mk659mod0, test set, steering assembly; mk556mod5, test set, cable; cable assembly w815; an/slq-32(v) 1, 2, 3 miscellaneous; misc parts list for dd 0983; misc parts elek for dd 0974

Pin Accommodation Length:

0.166 inches

Pin Accommodation Diameter:

Between 0.179 inches and 0.182 inches

Mounting Method:

Force fit

Product Name:

(dwg title) connectors, printed circuit subassembly and accessories: receptacle, socket contacts

Special Features:

Low insertion force contacts

Material:

Copper alloy body and contact

Precious Material And Location:

Body and contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Gold body and contact

Style Designator:

Socket contact

Terminal Type And Quantity:

1 crimp end opposite contact

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No