

View Online at <https://aerobasegroup.com/nsn/5999-01-491-8708>

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.162 inches and 0.182 inches

Overall Length:

Between 1.735 inches and 1.765 inches

Temperature Rating:

-55.0 degrees celsius and 125.0 degrees celsius

Overall Width:

Between 1.735 inches and 1.765 inches

Aperture Diameter:

Between 1.605 inches and 1.645 inches

Outside Corner Radius:

0.187 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.365 inches and 1.385 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.365 inches and 1.385 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.175 inches and 0.200 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.175 inches and 0.200 inches

Cross-sectional Height:

Between 0.027 inches and 0.037 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Material:

Rubber fluorosilicone class fq environmental seal

Precious Material And Location:

Emi/rfi conductive particles silver

Precious Material:

Silver

Surface Treatment:

Silver emi/rfi conductor

Style Designator:

Non-circular

Test Data Document:

81349-mil-g-83528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-g-83528/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0