# NSN 5999-01-537-3596

Tow-tag Operator Pa - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-537-3596

## **Overall Length:**

10.000 inches

### **Overall Height:**

5.000 inches

## **Overall Width:**

7.000 inches

#### **Environmental Protection:**

Watertight and fungus resistant and corrosion resistant to the salt atmosphere and hermetically sealed

#### **End Application:**

7457552 (53711), tagline/towline oper pack, l&rs

#### **Product Name:**

Inavy: tow/tag operator pack; dwg: towline/tagline oprator pack

## **Special Features:**

Nema 4x stainless steel enclosure; has ms4type proportional controller lever, spring return; 3 ms24523 3-position toggle switches, spring return; 1 ms24523 2-position toggle switch, spring return; 1 emergency stop guarded toggle switch (ms24524-23) and guard (ms25214-3); indicator light; connector assembly containing d38999/20wf11sb connector with fiber optic terminus, a sma type i connector, 1000 micron plastic fiber and wire pigtails; emi cover gasket; ms5423 emi-rfi shielded rubber boots for all toggle switches; a689 type sound powered headphone jack

## **Special Markings:**

53711-7457552-1, serial no.

#### Material:

Stainless steel

#### **General Description:**

Part of the remote control system used for launch and recovery system; uses latest state-of-the -art technology in fiber optic transmission; to be immune to emi and rfi per mil-std-461d; fitted with watertight emi gaskets and totally sealed - nema4x enclosure; operating ambient temp range: m25 to p125 degrees f; storage temp range: m40 to p140 degrees f

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli