

View Online at https://aerobasegroup.com/nsn/6060-01-383-3825

Fiber Optic Receptacle Connector - Page 1 of 2

Body Style:

Straight shape, fiber optic w/flange

Overall Length:

1.990 inches

Overall Height:

1.158 inches

Overall Width:

1.158 inches

Unthreaded Mounting Hole Diameter:

1.085 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.843 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.843 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

Tc-8 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Tempurature Rating:

Between -54.0 degrees celsius and 65.0 degrees celsius

Optical Fiber Attachment Method:

Friction single mating end single contact grouping

Optical Fiber Diameter Accommodated:

0.118 inches single mating end single contact grouping

Test Data Document:

81349-mil-c-28876d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-28876/1d government specification

Shelf Life:

N/a



Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-prf-28876 spec.