Fiber Optic Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6060-01-460-6002

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape threaded |
| Overall Length: |
| 1.990 inches |
| Overall Diameter: |
| Between 1.485 inches and 1.508 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 1.013 inches and 1.033 inches |
| Mounting Facility Thickness: |
| 0.188 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 4 single mating end |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 113.0 and 156.0 and 182.0 and 292.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| End Application: |
| An/ssq-9 (v) 4, cagec03950 |
| Thready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 1.000 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 4 single mating end single contact grouping |
| |

Fiber Optic Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape: Round w/flat Included Contact Type: Round socket single mating end single contact grouping Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0