NSN 6060-01-460-6006

Fiber Optic Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6060-01-460-6006 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.990 inches **Overall Diameter:** Between 1.485 inches and 1.508 inches **Distance From Mounting Shoulder To Front Face:** Between 1.013 inches and 1.033 inches **Mounting Facility Thickness:** 0.188 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 4 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 90.0 and 145.0 and 195.0 and 252.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** An/ssq-9 (v) 4, cagec03950 Thready Qty Per Inch (tpi): 20 **Thread Size:** 1.000 inches **Terminal Location:** Back single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

Included Contact Quantity:

4 single mating end single contact grouping

NSN 6060-01-460-6006

Fiber Optic Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0