Fiber Optic Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6060-01-460-6024

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape threaded
Overall Length:
1.990 inches
Overall Diameter:
Between 1.485 inches and 1.508 inches
Distance From Mounting Shoulder To Front Face:
Between 1.013 inches and 1.033 inches
Mounting Facility Thickness:
0.188 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
4 single mating end
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
53.0 and 156.0 and 220.0 and 255.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
End Application:
An/ssq-9 (v) 4, cagec03950
Thready Qty Per Inch (tpi):
20
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
4 single mating end single contact grouping

NSN 6060-01-460-6024

Fiber Optic Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape: Round w/flat Included Contact Type: Round socket single mating end single contact grouping Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0