NSN 6060-01-521-9553

Fiber Optic Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6060-01-521-9553

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.990 inches

Overall Height:

Between 1.236 inches and 1.278 inches

Overall Width:

Between 1.236 inches and 1.278 inches

Environmental Protection:

Weather resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.968 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.968 inches

Distance From Mounting Shoulder To Front Face:

Between 0.878 inches and 0.898 inches

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

119.0

End Application:

E/i can ees no. 15; wsd: seawolf class ssn

Operating Tempurature Rating:

Between -54.0 degrees celsius and 65.0 degrees celsius

Insert Material:

Rubber fluorosilicone class fq single mating end

Shell Material:

Aluminum alloy or stainless steel

Shell Surface Treatment:

Cadmium or passivate

Special Features:

One end dia. 1.255 inch; other end dia. 1.062 inch; center mtg hole dia. 1.124 inch; shell size 15; yellow color band

Test Data Document:

81349-mil-c-28876 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349 - mil-c-28876/1 government specification

NSN 6060-01-521-9553

Fiber Optic Receptacle Connector - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0