## NSN 6060-01-619-1231

Fiber Optic Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6060-01-619-1231



**Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 32.5 millimeters **Overall Diameter:** Between 37.8 millimeters and 38.4 millimeters **Distance From Mounting Shoulder To Front Face:** 22.6 millimeters **Threaded Device Type:** Mounting bushing **Mating End Quantity: Polarization Method:** Keyway or multiple keyway **Connector Locking Method:** Externally threaded shell **End Application:** B-2 bomber **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius **Features Provided:** Color band engagement indicator **Thread Size:** 25.0 millimeters **Terminal Location:** Back single mating end all contact groupings **Shell Surface Treatment:** Cadmium **Thread Tolerance Class:** 6g external **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Round socket single mating end all contact groupings **Special Features:** The shell finish is 500 hour salt spray resistant. The contacts include an alignment sleeve. Color: Olive drab **Thread Series Designator:** Iso m

## NSN 6060-01-619-1231

Fiber Optic Receptacle Connector - Page 2 of 2



Shelf L	ife:
---------	------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0