NSN 6105-00-080-5537

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-080-5537 **Overall Height:** 12.375 inches **Overall Length:** 19.750 inches **Overall Width:** 8.875 inches Thread Length: 0.7500 inches single end **Keyway Width:** 0.1880 inches single end **Keyway Depth:** 0.0940 inches single end **Shaft Diameter:** 0.6880 inches single end **Keyway Length:** 1.3120 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Dripproof protected-45 deg Winding Type: Shunt wound w/commutating poles-stabilizing windings **Mounting Method:** Fixed base **Mounting Facility Type And Quantity:** 4 unthreaded hole **Cooling Method:** Fan cooled **Inclosure Specificationification:** Mil-std-108 **Bearing Type:** Annular ball **Features Provided:** Vertical mounting position Frame Size Designation: 202e **Power Rating:** 1.0000 horsepower output

Thread Size:

0.500 inches single end

NSN 6105-00-080-5537Direct Current Motor - Page 2 of 2



Length Of Shaft From Housing:
6.125 inches single end
Shaft Center To Mounting Surface Distance:
4.625 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
5.500 inches
Tempurature Rating:
50.0 operating degrees celsius
Rotor Speed Rating In Rpm:
3450.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
8.000 inches
Connection Type And Voltage Rating In Volts:
250.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a9 second style single end
Thread Series Designator:
Unc single end
Terminal Type And Quantity:
3 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.