Alternating Current Motor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6105-00-081-5366

Shaft Rotation Direction: Clockwise single end Dury Cycle: Continuos Inclosure Feature: Open protected Winding Type: Induction-shaded pole Mounting Method: Resilien tradle Mounting Facility Type And Quantity: 4 slot Cooling Method: Amounting Specificationification: Corrent Rating Method: Load Mounting position and thermal protective device Roor Specificationification: Contern Rating In Appe: 1500.0 single full load Current Rating In Appe: 1500.0 single full load Current Rating In Appe: 1500.0 single full load Current Rating In Appe: 150.0 single single end Phase: Single input Foremery Hortz:		
Play Cycle: Continuous Inclosure Feature: Open protected Winding Type: Induction-shaded pole Munting Wethod: Resilien tradie Mounting Facility Type And Quantity: 4 slot Cooling Method: Ambient air Current Rating Method: Cording Method: Confine Conting Method: Cording Method: Control Stating In Stating In Method: Control Stating In Stating In Method: Commercial Pertors Provided: Roto Specificationification: Commercial Roto Specificationification: Commercial Pertors Provided: Vertical mounting position and thermal protective device Roto Specificationification: 150.0 no single full load Current Rating In Amps: 163.0 no noutral single input Shaft End Characteristic: Als single style single end Phase: Single input Stating In Spe And Quantity: Single input Phase:	Shaft Rotation Direction:	
Continuous Inclosure Feature: Open protected Winding Type: Induction-shaded pole Mounting Stabied pole Mounting Facility Type And Quantity: A solt Cooling Method: A solt Cooling Method: Ambient air Courrent Rating Method: Load Parters Provided: Commercial Features Provided: Vartical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Aups: 0-320 single input Prosection Type And Voltage Rating In Volts: 151.0 line to neutral single input Shingle style single end Phase: Single input Frequency in Hertz: 60.0 input Shingle Inical Variant Type And Quantity: Na Bigle input Frequency in Hertz: 60.0 input Commercial Frequency in Hertz: O input Curot Massere:	Clockwise single end	
Iclosure Feature: Open protected Winding Type: Induction-shaded pole Mounting Method: Resilient cradle Mounting Facility Type And Quantity: 4 slot Cooling Method: Ambient air Colling Method: Load Inclosure SpecificationIfication: Commercial Features Provided: Vertical mounting position and thermal protective device Retor SpecificationIfication: 1500. single full load Current Rating In Ange: 0-920 single full cad Current Rating In Ange: 0-920 single full cad Staft Ed Characteristic: 15.0 line to neutral single input Staft Ed Characteristic: 14.0 input Phase: Single input Frequency In Hertz: 6.0 input Staft IC Maasure: Na Surgle input Termed Type And Quantity: I single input Frequency In Hertz: 6.0 input Surine I single input	Duty Cycle:	
Open protected Winding Type: Induction-shaded pole Mounting Method: Resilient cradle Mounting Facility Type And Quantity: 4 slot Cooling Method: Amother Sacility Type And Quantity: 4 slot Cooling Method: Amother Sacility Type And Quantity: 4 slot Corent Rating Method: Load Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 10:00.00 single full load Corenction Type And Voltage Rating In Volts: 11:0 line to neutral single input Shaft End Characteristic: A3 single single single end Phase: Single input Frequency In Hertz: 60.01 put Fremil	Continuous	
Winding Type: Induction-shaded pole Mounting Method: Resilient cradle Mounting Facility Type And Quantity: 4 slot Cooling Method: Ambient air Current Rating Method: Load Inclosure Specificationfication: Commercial Features Provided: Vertical mounting position and thermal protective device Retor Speed Rating In Rpm: 1600.0 single full load Current Rating Ind Nups: 1050.0 single full load Current Rating In Apps: 1050.0 single full load Surrent Rating In Apps: 1050.0 single full load Partices In outral single input Shaft End Characteristic: Als single style single end Phase: Single input Frequency In Herz: 60.0 put Store full Sure lead Sherd Life: Na Info Measure: Info Measure: Info Measure: Info Measure: Na Na	Inclosure Feature:	
Induction-shaded pole Mounting Method: Resilient cradle Resilient cradle Mounting Facility Type And Quantity: 4 slot Cooling Method: Ambient ai Courrent Rating Method: Load Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single full load Current Rating in put Soft End Characteriste: As single style single end Phase: Single input Frequency In Hertz: Single input Soft End Characteriste: Single input Soft End Ch	Open protected	
Routing Method: Rosilient cradle Mouting Facility Type And Quantity: 4 slot Colling Method: Ambient air Current Rating Method: Load Inclosure Specificationification: Commercial Pattures Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.320 single input Pattures In Voltage Rating In Volts: 115.0 line to neutral single input Patter Anging style single end Phase: Single input Frequency In Metrz: 8.0.0 input Proved Metrz: 8.0.0 input Frequency In Metrz: 9.0 input Frequency In Metrz: 9.0 input Inf Of	Winding Type:	
Resilient anale 4 stot Coling Method: Ambient air Current Rating Method: Load Inclosure Specificationification: Commercial Fatures Provided: Vertical mounting position and thermal protective device Roro Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Pathoe: 15.0 line to neutral single input Phase: Single single and Phase: Single input Frequency In Metrz: 8.0.0 input Preview In Metrz: 8.0.1 input Frequency In Metrz: 8.0.2 input Frequency In Metrz: 8.0.1 input Frequency In Metrz: 8.0.2 input Frequency In Metrz: 8.0.1 input Frequency In Metrz: 8.0.1 input Frequency In Metrz: 9.0.2 input Frequency In Metrz: 10.1 for Measure: 10.1 for Measure: <th>Induction-shaded pole</th> <th></th>	Induction-shaded pole	
Mounting Facility Type And Quantity: 4 slot Cooling Method: Ambient air Current Rating Method: Load Incoure Specificationification: Commercial Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A3 single style single end Phase: Single input Go.0 input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shift life: Na Int Of Measure: r Penilitarization: No Fig:	Mounting Method:	
4 slot Cooling Method: Ambient air Current Rating Method: Load Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 80.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Pomilitarization: No Fig:	Resilient cradle	
Cooling Method: Ambient air Current Rating Method: Load Inclosure Specificationification: Commercial Features Provided: Varient Rating In Specification and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.s20 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Phase: Single input Prequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: Na Dird Measure: Int Of Measure: Image: Ferige:	Mounting Facility Type And Quantity:	
Ambient air Current Rating Method: Load Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and thermal protective device Retor Speed Rating In Rpm: Vertical mounting position and thermal protective device Retor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Errinal Type And Quantity: 3 wire lead Sheff Life: N/a Unit Of Measure: - Temilitarization: No	4 slot	
Current Rating Method: Load Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.320 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 30.0 input Ternical Type And Quantity: 3 vire lead Sheff Life: Iva Phase: Stord of Measure: Iva Frequency In Hertz: A0.0 input Tornical Type And Quantity: A wite Ivid Measure:	Cooling Method:	
Load Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Sheft Life: Na Sheft Life: Na Commercial Commer	Ambient air	
Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Jurit Contention: 3 wire lead Shelf Life: Iva Phase: 3 wire lead Shelf Life: Iva Din tof Measure: Iva Fig:	Current Rating Method:	
Commercial Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Forminal Type And Quantity: 3 wire lead Phafe: Va Init of Measure: r Phafe Infe: No Fig:	Load	
Features Provided: Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Concection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 6.0.0 input Terminal Type And Quantity: 3 wire lead Fuel Na Init of Measure: · Phase: Single Input Frequency In Hertz: A0 single Add Quantity: 3 wire lead Fuel Phase: Init of Measure: · Phase: Phase: Phase: Init of Measure: Phase: Phase: Phase: Phase: Phase: Phase: Phase: Phase: <t< th=""><th>Inclosure Specificationification:</th><th></th></t<>	Inclosure Specificationification:	
Vertical mounting position and thermal protective device Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Sheft Life: N/a Sheft Life: N/a Dint Of Measure: - Formilitarization: No Fig:	Commercial	
Rotor Speed Rating In Rpm: 1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit of Measure: - Pomilitarization: No Fig:	Features Provided:	
1500.0 single full load Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Frequency In Hertz: 3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Vertical mounting position and thermal protectiv	e device
Current Rating In Amps: 0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Sheft Life: N/a Unit Of Measure: - Poil Fig:	Rotor Speed Rating In Rpm:	
0.920 single input Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	1500.0 single full load	
Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Current Rating In Amps:	
115.0 line to neutral single input Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.920 single input	
Shaft End Characteristic: A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Connection Type And Voltage Rating In Volt	s:
A9 single style single end Phase: Single input Frequency In Hertz: 60.0 input Command Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	115.0 line to neutral single input	
Phase: Single input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Shaft End Characteristic:	
Single input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Fig:	A9 single style single end	
Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Phase:	
60.0 input Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Pomilitarization: No	Single input	
Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Frequency In Hertz:	
3 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	60.0 input	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:	
N/a Unit Of Measure: Demilitarization: No Fiig:	3 wire lead	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:		
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A271a0	Filg:	
	A271a0	