

NSN 6105-00-088-5080 Alternating Current Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6105-00-088-5080 **Overall Height:** 21.500 inches **Overall Length:** 29.313 inches **Overall Width:** 19.000 inches Thread Length: 0.5000 inches single end Step Diameter: 1.2500 inches single end Step Length: 0.5000 inches single end **Taper Length:** 2.0000 inches single end **Keyway Width:** 0.3750 inches single end **Keyway Depth:** 0.1880 inches single end **Shaft Diameter:** 2.0000 inches single end **Keyway Length:** 1.9380 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Totally enclosed Winding Type: Induction-squirrel cage

**Mounting Method:** 

**Mounting Facility Type And Quantity:** 

4 threaded hole

**Cooling Method:** 

Fan cooled

**Current Rating Method:** 

Load

**Inclosure Specificationification:** 

Mil-std-108

**Features Provided:** 

Vertical mounting position and thermal protective device and horizontal mounting position

## **NSN 6105-00-088-5080**Alternating Current Motor - Page 2 of 2



Power Rating:
26.6000 horsepower output
Taper:
0.625 per foot in inches single end
Length Of Shaft From Housing:
4.250 inches single end
Tempurature Rating:
50.0 operating degrees celsius and 65.0 ambient degrees celsius
Mounting Facility Circle Diameter:
12.000 inches
Rotor Speed Rating In Rpm:
1175.0 single full load
Current Rating In Amps:
40.000 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a29 second style single end and a12 third style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.