
# NSN 6105-00-196-4936

Direct Current Motor - Page 1 of 2





# **Overall Height:**

1.688 inches

# **Overall Width:**

1.500 inches

# Maximum Operating Altitude Rating:

50000.0 feet

## **Shaft Rotation Direction:**

Counterclockwise second end

#### **Duty Cycle:**

Intermittent

#### **Inclosure Feature:**

Totally enclosed

#### Winding Type:

Shunt wound

#### **Mounting Method:**

Face

## Mounting Facility Type And Quantity:

3 threaded hole

## Time Interval:

2.0 seconds on and 2.0 seconds off

## **Cooling Method:**

Nonventilated

# **Current Rating Method:**

Load

### **Torque Rating And Type:**

1.0 inch-ounces running

### Inclosure Specificationification:

Commercial

## Features Provided:

Vertical mounting position and horizontal mounting position

#### **Tempurature Rating:**

-55.0 operating degrees celsius and 55.0 operating degrees celsius

#### **Rotor Speed Rating In Rpm:**

12000.0 single full load

### **Current Rating In Amps:**

1.100 single input

# **Connection Type And Voltage Rating In Volts:**

26.5 line to neutral single input

# Shaft End Characteristic:

A24 single style second end

# Terminal Type And Quantity:

1 wire lead

# NSN 6105-00-196-4936

Direct Current Motor - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A271a0

