NSN 6105-00-222-4758

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-222-4758

| Overall Height: |
|---------------------------------------------------------------------------|
| 18.500 inches |
| Overall Length: |
| 31.562 inches |
| Overall Width: |
| 18.875 inches |
| Thread Length: |
| 1.0000 inches single end |
| Keyway Length: |
| 1.8750 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end or counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Watertight |
| Winding Type: |
| Induction-squirrel cage |
| Mounting Method: |
| Fixed base |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Cooling Method: |
| Fan cooled |
| Current Rating Method: |
| Load |
| Inclosure Specificationification: |
| Mil-std-108 |
| Features Provided: |
| Horizontal mounting position |
| Power Rating: |
| 7.8600 horsepower output |
| Thread Size: |
| 0.625 inches single end |
| Length Of Shaft From Housing: |
| 9.500 inches single end |
| Shaft Center To Mounting Surface Distance: |
| 8.000 inches single end |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 10.500 inches |
| Tempurature Rating: |

50.0 operating degrees celsius and 45.0 ambient degrees celsius

NSN 6105-00-222-4758

Demilitarization:

Mil-std-108 spec.

Mil-std (military Standard):

No Fiig: A271a0

Alternating Current Motor - Page 2 of 2



| Rotor Speed Rating In Rpm: |
|-----------------------------------------------------------------------------------------|
| 1900.0 single no load and 1740.0 single full load |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 12.500 inches |
| Current Rating In Amps: |
| 11.050 single input |
| Connection Type And Voltage Rating In Volts: |
| 440.0 line to neutral single input |
| Shaft End Characteristic: |
| A2 first style single end and a9 second style single end and a12 third style single end |
| Phase: |
| Three input |
| Special Features: |
| Lh thd. On end of armature shaft |
| Frequency In Hertz: |
| 60.0 input |
| Thread Series Designator: |
| Unf single end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |