Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-229-5497

#### **Overall Height:**

11.125 inches

#### liilength:

20.938 inches

## **Overall Width:**

14.875 inches

#### Thread Length:

0.7500 inches single end

#### **Taper Length:**

1.1880 inches single end

#### Keyway Width:

0.3120 inches single end

#### Keyway Depth:

0.3120 inches single end

#### Shaft Diameter:

0.750 inches single end and 1.063 inches single end

#### Shaft Rotation Direction:

Clockwise single end or counterclockwise single end

#### **Duty Cycle:**

Continuous

#### Inclosure Feature:

Totally enclosed

#### Winding Type:

Induction-squirrel cage

#### **Mounting Method:**

End bell

#### Mounting Facility Type And Quantity:

4 unthreaded hole

#### **Cooling Method:**

Ambient air

#### Inclosure Specificationification:

Mil-std-108

#### **Features Provided:**

Vertical mounting position and horizontal mounting position

#### **Power Rating:**

2.0000 horsepower output

#### **Thread Size:**

0.750 inches single end

#### Taper:

1.500 per foot in inches single end

#### Length Of Shaft From Housing:

3.062 inches single end

# NSN 6105-00-229-5497

Alternating Current Motor - Page 2 of 2



#### **Tempurature Rating:**

50.0 operating degrees celsius and 40.0 ambient degrees celsius

### Mounting Facility Circle Diameter:

5.000 inches

## Rotor Speed Rating In Rpm:

1740.0 single full load

## Connection Type And Voltage Rating In Volts:

440.0 line to neutral single input

## Shaft End Characteristic:

A2 single style single end and a29 first style single end

Phase:

Three input

#### Frequency In Hertz:

60.0 input

#### **Thread Series Designator:**

Unf single end

#### **Terminal Type And Quantity:**

3 wire lead

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A271a0

#### Mil-std (military Standard):

Mil-std-108 spec.