NSN 6105-00-235-2854

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-235-2854 **Overall Height:** 25.500 inches **Overall Length:** 35.688 inches **Overall Width:** 24.625 inches **Keyway Width:** 0.5000 inches single end **Keyway Depth:** 0.2500 inches single end **Shaft Diameter:** 1.8750 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Totally enclosed Specific Use: Aux circulating pump Winding Type: Induction-squirrel cage **Mounting Method:** Flange **Mounting Facility Type And Quantity:** 4 unthreaded hole **Cooling Method:** Fan cooled **Current Rating Method:** Load **Inclosure Specificationification:** Mil-std-108 **Bearing Type:** Annular ball **Features Provided:** Vertical mounting position **Length Of Shaft From Housing:** 0.000 inches single end **Tempurature Rating:**

50.0 operating degrees celsius and 45.0 ambient degrees celsius **Mounting Facility Circle Diameter:**

22.000 inches

NSN 6105-00-235-2854

Alternating Current Motor - Page 2 of 2



Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A9 single style single end
Phase:
Three input
Special Features:
Shaft extends 2.625 in. From brg housing
Frequency In Hertz:
60.0 input
Test Data Document:
81349-mil-m-17060 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
6 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.