Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-236-6607

Overall Height:
13.234 inches
Overall Length:
15.688 inches
Overall Width:
13.234 inches
Thread Length:
1.0000 inches single end
Hole Diameter:
0.1560 inches single end
Hole Depth:
0.6250 inches single end
Taper Length:
2.5620 inches single end
Keyway Width:
0.2500 inches single end
Keyway Depth:
0.1250 inches single end
Shaft Diameter:
1.0000 inches single end
Keyway Length:
2.0000 inches single end
Hole Center To Shaft End Distance:
0.3120 inches single end
Shaft Rotation Direction:
Clockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Watertight
Winding Type:
Induction-squirrel cage
Cooling Method:
Ambient air
Inclosure Specificationification:
Mil-std-108
Features Provided:
Vertical mounting position
Power Rating:
1.0000 horsepower output
Thread Size:
0.625 inches single end

## NSN 6105-00-236-6607

Alternating Current Motor - Page 2 of 2



Taper:	
0.625	per foot in inches single end
Lengtl	h Of Shaft From Housing:
3.938 i	inches single end
Shaft	Center To Mounting Surface Distance:
6.625 i	inches single end
Tempu	urature Rating:
65.0 oj	perating degrees celsius and 30.0 ambient degrees celsius
Rotor	Speed Rating In Rpm:
3500.0	) single full load
Conne	ection Type And Voltage Rating In Volts:
440.0 l	line to neutral single input
Shaft	End Characteristic:
A2 first	t style single end and a13 second style single end and a29 third style single end
Phase	:
Three	input
Specia	al Features:
Motor	housing pushed fit into mounting frame
Freque	ency In Hertz:
60.0 in	put
Thread	d Series Designator:
Unf sir	ngle end
Termiı	nal Type And Quantity:
3 solde	er lug
Shelf I	Life:
N/a	
Unit O	f Measure:
Demili	itarization:
No	
Fiig:	
A271a	0
Mil-sto	d (military Standard):
Mil-std	-108 spec.