NSN 6105-00-238-2979

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-238-2979

Overall Height:			
10.875 inches			
Overall Length:			
20.000 inches			
Overall Width:			
10.750 inches			
Shaft Diameter:			
1.0000 inches single end			
Shaft Rotation Direction:			
Clockwise single end or counterclockwise single end			
Duty Cycle:			
Continuous			
Inclosure Feature:			
Dripproof-15 deg			
Winding Type:			
Compound wound			
Mounting Method:			
Fixed base			
Mounting Facility Type And Quantity:			
4 unthreaded hole			
Current Rating Method:			
Load			
Load Inclosure Specificationification:			
Inclosure Specificationification:			
Inclosure Specificationification: Commercial			
Inclosure Specificationification: Commercial Power Rating:			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing:			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance:			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 9.000 inches			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 9.000 inches Tempurature Rating:			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 9.000 inches Tempurature Rating: 60.0 ambient degrees celsius and 40.0 operating degrees celsius			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 9.000 inches Tempurature Rating: 60.0 ambient degrees celsius and 40.0 operating degrees celsius Rotor Speed Rating In Rpm:			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 9.000 inches Tempurature Rating: 60.0 ambient degrees celsius and 40.0 operating degrees celsius Rotor Speed Rating In Rpm: 1150.0 single full load			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 9.000 inches Tempurature Rating: 60.0 ambient degrees celsius and 40.0 operating degrees celsius Rotor Speed Rating In Rpm: 1150.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width:			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 9.000 inches Tempurature Rating: 60.0 ambient degrees celsius and 40.0 operating degrees celsius Rotor Speed Rating In Rpm: 1150.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 7.500 inches			
Inclosure Specificationification: Commercial Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 3.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 9.000 inches Tempurature Rating: 60.0 ambient degrees celsius and 40.0 operating degrees celsius Rotor Speed Rating In Rpm: 1150.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 7.500 inches Current Rating In Amps:			

NSN 6105-00-238-2979

Direct Current Motor - Page 2 of 2



~ : <i>•</i>		•	
Shat.	t Hnd	('hars	acteristic

A1 single style single end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0