Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-238-4562

 2.438 inches Overall Length: 3.063 inches Overall Width: 2.438 inches Shaft Diameter: 0.1870 inches single end and 0.1875 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output Length Of Shaft From Housing:
 3.063 inches Overall Width: 2.438 inches Shaft Diameter: 0.1870 inches single end and 0.1875 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Overall Width:2.438 inchesShaft Diameter:0.1870 inches single end and 0.1875 inches single endShaft Rotation Direction:Clockwise single end or counterclockwise single endDuty Cycle:ContinuousInclosure Feature:Totally enclosedWinding Type:Induction-squirrel cageMounting Facility Type And Quantity:4 threaded studInclosure Specificationification:CommercialPower Rating:0.0250 horsepower output
 2.438 inches Shaft Diameter: 0.1870 inches single end and 0.1875 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Shaft Diameter: 0.1870 inches single end and 0.1875 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
 0.1870 inches single end and 0.1875 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Totally enclosed Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Winding Type: Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Induction-squirrel cage Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Mounting Facility Type And Quantity: 4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
4 threaded stud Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Inclosure Specificationification: Commercial Power Rating: 0.0250 horsepower output
Commercial Power Rating: 0.0250 horsepower output
Power Rating: 0.0250 horsepower output
0.0250 horsepower output
Length Of Shaft From Housing:
0.438 inches single end
Tempurature Rating:
50.0 operating degrees celsius and 40.0 ambient degrees celsius
Mounting Facility Circle Diameter:
2.688 inches
Rotor Speed Rating In Rpm:
1800.0 single full load
Connection Type And Voltage Rating In Volts:
115.0 line to neutral single input
Shaft End Characteristic:
A1 single style single end
Phase:
Single input
Frequency In Hertz:
60.0 input
Shelf Life:
N/a
Unit Of Measure:
-

NSN 6105-00-238-4562

Alternating Current Motor - Page 2 of 2

Demilitarization:

No

Fiig:

A271a0

