## NSN 6105-00-239-4184

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-239-4184

Overall Height: 2.125 inches Overall Length: 4.781 inches Overall Width: 1.875 inches Maximum Operating Altitude Rating: 50000.0 feet Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: Alt4 single style single end Shaft I ife-	
Overall Length: 4.781 inches Overall Width: 1.875 inches Maximum Operating Altitude Rating: 50000.0 feet Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Overall Height:
4.781 inches Overall Width: 1.875 inches Maximum Operating Altitude Rating: 50000.0 feet Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	2.125 inches
Overall Width:  1.875 inches  Maximum Operating Altitude Rating: 50000.0 feet  Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Overall Length:
1.875 inches  Maximum Operating Altitude Rating: 50000.0 feet  Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	4.781 inches
Maximum Operating Altitude Rating: 50000.0 feet Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Overall Width:
Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	1.875 inches
Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Maximum Operating Altitude Rating:
Clockwise single end or counterclockwise single end  Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	50000.0 feet
Duty Cycle: Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Shaft Rotation Direction:
Intermittent Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Clockwise single end or counterclockwise single end
Inclosure Feature: Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Duty Cycle:
Totally enclosed Winding Type: Series wound Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Intermittent
Winding Type: Series wound  Mounting Method: Flange  Mounting Facility Type And Quantity: 4 unthreaded hole  Current Rating Method: Load  Features Provided: Thermal protective device  Power Rating: 0.1740 horsepower output  Length Of Shaft From Housing: 0.625 inches single end  Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter: 1.500 inches  Rotor Speed Rating In Rpm: 11000.0 single full load  Current Rating In Amps: 9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	Inclosure Feature:
Series wound  Mounting Method: Flange  Mounting Facility Type And Quantity: 4 unthreaded hole  Current Rating Method: Load  Features Provided: Thermal protective device  Power Rating: 0.1740 horsepower output  Length Of Shaft From Housing: 0.625 inches single end  Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter: 1.500 inches  Rotor Speed Rating In Rpm: 11000.0 single full load  Current Rating In Amps: 9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	Totally enclosed
Mounting Method: Flange Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Winding Type:
Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Series wound
Mounting Facility Type And Quantity: 4 unthreaded hole Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Mounting Method:
4 unthreaded hole  Current Rating Method: Load  Features Provided: Thermal protective device  Power Rating: 0.1740 horsepower output  Length Of Shaft From Housing: 0.625 inches single end  Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter: 1.500 inches  Rotor Speed Rating In Rpm: 11000.0 single full load  Current Rating In Amps: 9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	Flange
Current Rating Method: Load Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Mounting Facility Type And Quantity:
Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	4 unthreaded hole
Features Provided: Thermal protective device Power Rating: 0.1740 horsepower output Length Of Shaft From Housing: 0.625 inches single end Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius Mounting Facility Circle Diameter: 1.500 inches Rotor Speed Rating In Rpm: 11000.0 single full load Current Rating In Amps: 9.000 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end	Current Rating Method:
Thermal protective device  Power Rating:  0.1740 horsepower output  Length Of Shaft From Housing:  0.625 inches single end  Tempurature Rating:  -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter:  1.500 inches  Rotor Speed Rating In Rpm:  11000.0 single full load  Current Rating In Amps:  9.000 single input  Connection Type And Voltage Rating In Volts:  26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	Load
Power Rating:  0.1740 horsepower output  Length Of Shaft From Housing:  0.625 inches single end  Tempurature Rating:  -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter:  1.500 inches  Rotor Speed Rating In Rpm:  11000.0 single full load  Current Rating In Amps:  9.000 single input  Connection Type And Voltage Rating In Volts:  26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	Features Provided:
0.1740 horsepower output  Length Of Shaft From Housing: 0.625 inches single end  Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter: 1.500 inches  Rotor Speed Rating In Rpm: 11000.0 single full load  Current Rating In Amps: 9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	Thermal protective device
Length Of Shaft From Housing:  0.625 inches single end  Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter: 1.500 inches  Rotor Speed Rating In Rpm: 11000.0 single full load  Current Rating In Amps: 9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	Power Rating:
0.625 inches single end  Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter: 1.500 inches  Rotor Speed Rating In Rpm: 11000.0 single full load  Current Rating In Amps: 9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	0.1740 horsepower output
Tempurature Rating: -50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter: 1.500 inches  Rotor Speed Rating In Rpm: 11000.0 single full load  Current Rating In Amps: 9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	Length Of Shaft From Housing:
-50.0 operating degrees celsius and 70.0 operating degrees celsius  Mounting Facility Circle Diameter:  1.500 inches  Rotor Speed Rating In Rpm:  11000.0 single full load  Current Rating In Amps:  9.000 single input  Connection Type And Voltage Rating In Volts:  26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	0.625 inches single end
Mounting Facility Circle Diameter:  1.500 inches  Rotor Speed Rating In Rpm:  11000.0 single full load  Current Rating In Amps:  9.000 single input  Connection Type And Voltage Rating In Volts:  26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	Tempurature Rating:
1.500 inches  Rotor Speed Rating In Rpm:  11000.0 single full load  Current Rating In Amps:  9.000 single input  Connection Type And Voltage Rating In Volts:  26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	-50.0 operating degrees celsius and 70.0 operating degrees celsius
Rotor Speed Rating In Rpm:  11000.0 single full load  Current Rating In Amps:  9.000 single input  Connection Type And Voltage Rating In Volts:  26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	Mounting Facility Circle Diameter:
11000.0 single full load  Current Rating In Amps: 9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	1.500 inches
Current Rating In Amps:  9.000 single input  Connection Type And Voltage Rating In Volts:  26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	Rotor Speed Rating In Rpm:
9.000 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end	11000.0 single full load
Connection Type And Voltage Rating In Volts:  26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	Current Rating In Amps:
26.0 line to neutral single input  Shaft End Characteristic:  A14 single style single end	9.000 single input
Shaft End Characteristic: A14 single style single end	Connection Type And Voltage Rating In Volts:
A14 single style single end	26.0 line to neutral single input
	Shaft End Characteristic:
	A14 single style single end
Olion Elio.	Shelf Life:

N/a

## NSN 6105-00-239-4184

Direct Current Motor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A271a0