NSN 6105-00-241-4979



Direct Current Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6105-00-241-4979

Overall Height:
8.781 inches
Overall Length:
13.938 inches
Overall Width:
8.500 inches
Thread Length:
0.3750 inches single end
Step Diameter:
0.6250 inches single end
Step Length:
2.7500 inches single end
Keyway Width:
0.1880 inches single end
Keyway Depth:
0.0940 inches single end
Shaft Diameter:
0.7500 inches single end
Keyway Length:
1.8750 inches single end
Shaft Rotation Direction:
Clockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Dripproof protected-45 deg
Winding Type:
Compound wound
Mounting Method:
Adjustable base
Mounting Facility Type And Quantity:
4 slot
Cooling Method:
Self-ventilated
Current Rating Method:
Load
Inclosure Specificationification:
Mil-std-108
Features Provided:
Frame electrically grounded and horizontal mounting position and vertical mounting position
Power Rating:
0.2500 horsepower output

NSN 6105-00-241-4979

Direct Current Motor - Page 2 of 2



Thread Size:
0.500 inches single end
Length Of Shaft From Housing:
4.438 inches single end
Shaft Center To Mounting Surface Distance:
3.500 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches
Tempurature Rating:
40.0 ambient degrees celsius and 50.0 operating degrees celsius
Rotor Speed Rating In Rpm:
1725.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.875 inches
Current Rating In Amps:
2.600 single input
Connection Type And Voltage Rating In Volts:
115.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a9 second style single end and a12 third style single end
Thread Series Designator:
Unf single end
Terminal Type And Quantity:
1 connector, plug
Specification Or Standard:
A service
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.