NSN 6105-00-241-5253

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-241-5253

View Online at https://aerobasegroup.com/nsn/6105-00-241-
Overall Length:
13.156 inches
Thread Length:
1.0000 inches single end
Step Diameter:
0.624 inches single end and 0.625 inches single end
Step Length:
1.0000 inches single end
Keyway Width:
0.1880 inches single end
Keyway Depth:
0.1880 inches single end
Shaft Diameter:
0.6245 inches single end and 0.6250 inches single end
Keyway Length:
1.5000 inches single end
Shaft Rotation Direction:
Counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Explosion proof
Winding Type:
Compound wound
Mounting Method:
Flange
Mounting Facility Type And Quantity:
4 threaded hole
Cooling Method:
Fan cooled
Current Rating Method:
Load
Inclosure Specificationification:
Mil-std-108
Features Provided:
Vertical mounting position and horizontal mounting position
Power Rating:
0.2000 horsepower output
Thread Size:
0.500 inches single end
Length Of Shaft From Housing:

3.312 inches single end

NSN 6105-00-241-5253

Direct Current Motor - Page 2 of 2

Mil-std-108 spec.



Tempurature Rating:
50.0 ambient degrees celsius and 50.0 operating degrees celsius
Mounting Facility Circle Diameter:
6.281 inches
Rotor Speed Rating In Rpm:
3300.0 single full load
Current Rating In Amps:
1.300 single input
Connection Type And Voltage Rating In Volts:
230.0 line to neutral single input
Shaft End Characteristic:
$\ensuremath{A2}$ first style single end and a9 second style single end and a12 third style single end
Thread Series Designator:
Unc single end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):