NSN 6105-00-241-5785

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-241-5785

| Overall Height: |
|---|
| 10.875 inches |
| Overall Length: |
| 18.000 inches |
| Overall Width: |
| 14.500 inches |
| Keyway Width: |
| 0.2500 inches single end |
| Keyway Depth: |
| 0.1250 inches single end |
| Shaft Diameter: |
| 1.0000 inches single end |
| Keyway Length: |
| 1.2500 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end or counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Totally enclosed |
| Specific Use: |
| Fuel oil transfer and purifier pump |
| Winding Type: |
| Compound wound |
| Mounting Method: |
| Fixed base |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Cooling Method: |
| Self-ventilated |
| Current Rating Method: |
| Load |
| Inclosure Specificationification: |
| Mil-std-108 |
| Bearing Type: |
| Annular ball |
| Features Provided: |
| Horizontal mounting position |
| Power Rating: |
| 1.0000 horsepower output |
| Length Of Shaft From Housing: |
| 4 500 in the stands and |

1.500 inches single end

NSN 6105-00-241-5785 Direct Current Motor - Page 2 of 2



| 5.50 | 00 inches single end |
|------|--|
| Cer | nter To Center Distance Between Mounting Facilities Parallel To Length |
| 6.7 | 50 inches |
| Ten | npurature Rating: |
| 50.0 | 0 operating degrees celsius |
| Rot | tor Speed Rating In Rpm: |
| 115 | 50.0 single full load |
| Cer | nter To Center Distance Between Mounting Facilities Parallel To Width: |
| 9.00 | 00 inches |
| Cur | rrent Rating In Amps: |
| 4.10 | 00 single input |
| Соі | nnection Type And Voltage Rating In Volts: |
| 250 | 0.0 line to neutral single input |
| Sha | aft End Characteristic: |
| A9 | single style single end |
| She | elf Life: |
| N/a | |
| Uni | it Of Measure: |
| | |
| Der | militarization: |
| No | |
| Fiig | g: |
| A27 | 71a0 |
| Mil | -std (military Standard): |
| Mil- | -std-108 spec. |