NSN 6105-00-241-6585

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-241-6585

Overall Height:
1.531 inches
Overall Length:
3.531 inches
Overall Width:
2.219 inches
Shaft Diameter:
0.1562 inches single end
Teeth Quantity:
8 single end
Maximum Operating Altitude Rating:
35000.0 feet
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Intermittent
Inclosure Feature:
Explosion proof
Winding Type:
Series wound
Mounting Method:
Flance
Flange
Mounting Facility Type And Quantity:
-
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 unthreaded hole
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval:
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method:
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method:
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type:
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type: 0.1 inch-ounces stalled
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type: 0.1 inch-ounces stalled Inclosure Specificationification:
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type: 0.1 inch-ounces stalled Inclosure Specificationification: Commercial
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type: 0.1 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided:
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type: 0.1 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Electric noise suppressor and horizontal mounting position and vertical mounting position
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type: 0.1 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Electric noise suppressor and horizontal mounting position and vertical mounting position Power Rating:
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type: 0.1 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Electric noise suppressor and horizontal mounting position and vertical mounting position Power Rating: 0.0250 horsepower output
Mounting Facility Type And Quantity: 4 unthreaded hole Time Interval: 3.0 minutes on and 17.0 minutes off Cooling Method: Ambient air Current Rating Method: Load Torque Rating And Type: 0.1 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Electric noise suppressor and horizontal mounting position and vertical mounting position Power Rating: 0.0250 horsepower output Length Of Shaft From Housing:

NSN 6105-00-241-6585Direct Current Motor - Page 2 of 2



Mounting Facility Circle Diameter:
1.844 inches
Rotor Speed Rating In Rpm:
15000.0 single full load
Current Rating In Amps:
2.000 single input
Connection Type And Voltage Rating In Volts:
26.0 line to neutral single input
Shaft End Characteristic:
A23 single style single end
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0