NSN 6105-00-243-6596

Direct Current Motor - Page 1 of 2

Overall Height: 14.375 inches

3500.0 single full load



View Online at https://aerobasegroup.com/nsn/6105-00-243-6596

Overall Length:
21.812 inches
Overall Width:
9.844 inches
Thread Length:
0.8120 inches single end
Step Diameter:
0.9690 inches single end
Shaft Diameter:
1.0000 inches single end
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Splash proof
Winding Type:
Compound wound
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Current Rating Method:
Load
Inclosure Specificationification:
Commercial
Features Provided:
Vertical mounting position and horizontal mounting position
Power Rating:
1.5000 horsepower output
Length Of Shaft From Housing:
5.250 inches single end
Shaft Center To Mounting Surface Distance:
5.000 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.500 inches
Tempurature Rating:
50.0 ambient degrees celsius and 40.0 operating degrees celsius
Rotor Speed Rating In Rpm:

NSN 6105-00-243-6596

Direct Current Motor - Page 2 of 2



Contor	To Contor	Dictance	Rotwoon	Mounting	Escilition	Parallel To	Width.
Center	i o center	Distalle	DerMeell	wounting	racillities	raiallel I	, widtii.

8.000 inches

Current Rating In Amps:

6.950 single input

Connection Type And Voltage Rating In Volts:

220.0 line to neutral single input

Shaft End Characteristic:

A9 first style single end and a2 second style single end and a12 third style single end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0