NSN 6105-00-295-2009

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-295-2009

| Overall Height: |
|--|
| 12.562 inches |
| Overall Length: |
| 16.626 inches |
| Overall Width: |
| 9.906 inches |
| Shaft Diameter: |
| 0.7500 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Open |
| Winding Type: |
| Compound wound |
| Mounting Method: |
| Fixed base |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Current Rating Method: |
| Load |
| Inclosure Specificationification: |
| Nema |
| Features Provided: |
| Vertical mounting position and horizontal mounting position |
| Power Rating: |
| Tower Nating. |
| 1.0000 horsepower output |
| |
| 1.0000 horsepower output |
| 1.0000 horsepower output Length Of Shaft From Housing: |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: 5.000 inches single end |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: 5.000 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: 5.000 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: 5.000 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: 5.000 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: 5.000 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm: |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: 5.000 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm: 1750.0 single full load |
| 1.0000 horsepower output Length Of Shaft From Housing: 2.438 inches single end Shaft Center To Mounting Surface Distance: 5.000 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 5.500 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm: 1750.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: |

NSN 6105-00-295-2009

Direct Current Motor - Page 2 of 2



Connection Type And Voltage Rating In Volts:

230.0 line to neutral single input

Shaft End Characteristic:

A9 single style single end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0