## NSN 6105-00-446-8952



Direct Current Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6105-00-446-8952 **Overall Height:** 10.000 inches **Overall Length:** 21.000 inches **Overall Width:** 12.500 inches **Thread Length:** 0.7500 inches single end **Keyway Width:** 0.1880 inches single end **Keyway Depth:** 0.0940 inches single end

**Shaft Diameter:** 0.749 inches single end

**Keyway Length:** 

1.0000 inches single end

**Shaft Rotation Direction:** 

Clockwise single end or counterclockwise single end

**Duty Cycle:** 

Continuous

**Inclosure Feature:** 

Dripproof-15 deg

Winding Type:

Shunt wound

**Mounting Method:** 

Fixed base

**Mounting Facility Type And Quantity:** 

4 unthreaded hole

**Cooling Method:** 

Self-ventilated

**Current Rating Method:** 

**Inclosure Specificationification:** 

Mil-std-108

**Features Provided:** 

Vertical mounting position

Frame Size Designation:

204

**Power Rating:** 

1.2500 horsepower output

**Thread Size:** 

0.375 inches single end

## **NSN 6105-00-446-8952**Direct Current Motor - Page 2 of 2



Length Of Shaft From Housing:
1.219 inches single end
Shaft Center To Mounting Surface Distance:
5.000 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.500 inches
Tempurature Rating:
50.0 operating degrees celsius
Rotor Speed Rating In Rpm:
2650.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
8.000 inches
Current Rating In Amps:
10.500 single input
Connection Type And Voltage Rating In Volts:
120.0 line to neutral single input
Shaft End Characteristic:
A3 first style single end and a9 second style single end
Thread Series Designator:
Unf single end
Terminal Type And Quantity:
6 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.