NSN 6105-00-465-6162

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-465-6162

| Overall Height: |
|---|
| 6.330 inches |
| Overall Length: |
| 12.630 inches |
| Overall Width: |
| 6.500 inches |
| Keyway Width: |
| 0.1880 inches single end |
| Keyway Depth: |
| 0.0940 inches single end |
| Shaft Diameter: |
| 0.6250 inches single end |
| Keyway Length: |
| 1.3800 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end or counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Dripproof protected-15 deg |
| Winding Type: |
| Induction-squirrel cage |
| Mounting Method: |
| Resilient cradle |
| Mounting Facility Type And Quantity: |
| 4 slot |
| Cooling Method: |
| Self-ventilated |
| Inclosure Specificationification: |
| Nema |
| Features Provided: |
| Thermal protective device and horizontal mounting position and vertical mounting position |
| Frame Size Designation: |
| 56 |
| Power Rating: |
| 0.7500 horsepower output |
| Length Of Shaft From Housing: |
| 1.880 inches single end |
| Shaft Center To Mounting Surface Distance: |
| 3.000 inches single end |
| Center To Center Distance Retween Mounting Excilities Parallel To Length |

2.760 inches

NSN 6105-00-465-6162

Fiig: A271a0

Alternating Current Motor - Page 2 of 2



| Rotor Speed Rating In Rpm: |
|---|
| 3450.0 single full load |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.880 inches |
| Connection Type And Voltage Rating In Volts: |
| 230.0 line to neutral first multiple input or 460.0 line to neutral second multiple input |
| Shaft End Characteristic: |
| A9 single style single end |
| Phase: |
| Three input |
| Frequency In Hertz: |
| 60.0 input |
| Terminal Type And Quantity: |
| 9 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |