Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-500-0534

_	
	overall Height:
-	.940 inches
	overall Length:
	2.430 inches
-	overall Width:
	2.690 inches
	pline Minor Diameter:
	.4200 inches single end
S	pline Quantity:
1	1 single end
S	haft Diameter:
0	.5000 inches single end
S	haft Rotation Direction:
С	lockwise single end
D	outy Cycle:
С	Continuous
Ir	nclosure Feature:
Т	otally enclosed
V	Vinding Type:
Ir	nduction-squirrel cage
S	pline Length:
0	.5300 inches single end
N	Iounting Method:
F	ixed base and face
N	Iounting Facility Type And Quantity:
4	threaded stud and 4 unthreaded hole
С	cooling Method:
Ν	lonventilated
Ir	nclosure Specificationification:
N	fil-std-108
В	earing Type:
A	nnular ball
F	eatures Provided:
Н	lorizontal mounting position
Ρ	ower Rating:
0	.7500 horsepower output
L	ength Of Shaft From Housing:
0	.530 inches single end
S	haft Center To Mounting Surface Distance:
5	.000 inches single end
С	enter To Center Distance Between Mounting Facilities Parallel To Length:
5	.500 inches

NSN 6105-00-500-0534 Alternating Current Motor - Page 2 of 2



Tempurature Rating:
40.0 operating degrees celsius and 55.0 ambient degrees celsius
Mounting Facility Circle Diameter:
3.250 inches
Rotor Speed Rating In Rpm:
1755.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
8.000 inches
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A14 single style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.