

View Online at <https://aerobasegroup.com/nsn/6105-00-500-0716>

**Overall Height:**

9.750 inches

**Overall Length:**

18.937 inches

**Overall Width:**

12.750 inches

**Thread Length:**

0.5000 inches single end

**Shaft Diameter:**

0.6250 inches single end

**Shaft Rotation Direction:**

Clockwise single end

**Duty Cycle:**

Continuous

**Inclosure Feature:**

Totally enclosed

**Winding Type:**

Induction-squirrel cage

**Mounting Method:**

Fixed base

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Cooling Method:**

Ambient air

**Inclosure Specification:**

Mil-std-108

**Features Provided:**

Horizontal mounting position

**Power Rating:**

0.7500 horsepower output

**Thread Size:**

0.500 inches single end

**Length Of Shaft From Housing:**

6.187 inches single end

**Shaft Center To Mounting Surface Distance:**

5.000 inches single end

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.500 inches

**Temperature Rating:**

50.0 operating degrees celsius and 45.0 ambient degrees celsius

**Rotor Speed Rating In Rpm:**

3570.0 single full load

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

8.000 inches

**Connection Type And Voltage Rating In Volts:**

440.0 line to neutral single input

**Shaft End Characteristic:**

A2 first style single end and a11 second style single end and a12 third style single end

**Phase:**

Three input

**Frequency In Hertz:**

60.0 input

**Test Data Document:**

81349-mil-m-1940 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A271a0

**Mil-std (military Standard):**

Mil-std-108 spec.