NSN 6105-00-500-1239

Direct Current Motor - Page 1 of 2

Overall Height:

Tempurature Rating:

40.0 ambient degrees celsius and 50.0 operating degrees celsius



View Online at https://aerobasegroup.com/nsn/6105-00-500-1239

Overall Length: 31.500 inches Overall Width: 25.562 inches Keyway Width: 0.3750 inches single end Keyway Depth: 0.5000 inches single end Shaft Diameter: 2.0000 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end	25.500) inches
Overall Width: 25.562 inches Keyway Width: 0.3750 inches single end Keyway Depth: 0.5000 inches single end Shaft Diameter: 2.0000 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Overa	II Length:
25.562 inches Keyway Width: 0.3750 inches single end Keyway Depth: 0.5000 inches single end Shaft Diameter: 2.0000 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	31.500	inches
Keyway Width: 0.3750 inches single end Keyway Depth: 0.5000 inches single end Shaft Diameter: 2.0000 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Overa	II Width:
0.3750 inches single end Keyway Depth: 0.5000 inches single end Shaft Diameter: 2.0000 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	25.562	2 inches
Keyway Depth: 0.5000 inches single end Shaft Diameter: 2.0000 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Keywa	ay Width:
0.5000 inches single end Shaft Diameter: 2.0000 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	0.3750	inches single end
Shaft Diameter: 2.0000 inches single end Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Keywa	ay Depth:
Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	0.5000) inches single end
Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Shaft	Diameter:
Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	2.0000) inches single end
Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Shaft	Rotation Direction:
Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Clockv	vise single end or counterclockwise single end
Inclosure Feature: Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Duty C	Cycle:
Dripproof-15 deg Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Contin	uous
Winding Type: Compound wound Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Inclos	ure Feature:
Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Drippro	oof-15 deg
Mounting Method: Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Windi	ng Type:
Fixed base Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Compo	ound wound
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Mount	ting Method:
4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Fixed I	base
Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Mount	ting Facility Type And Quantity:
Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	4 unth	readed hole
Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Coolin	ng Method:
Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Self-ve	entilated
Inclosure Specificationification: Mil-std-108 Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Curre	nt Rating Method:
Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Load	
Features Provided: Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Inclos	ure Specificationification:
Vertical mounting position Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Mil-std	I-108
Power Rating: 20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Featur	res Provided:
20.0000 horsepower output Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Vertica	al mounting position
Length Of Shaft From Housing: 6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Power	Rating:
6.500 inches single end Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	20.000	00 horsepower output
Shaft Center To Mounting Surface Distance: 11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	Lengtl	h Of Shaft From Housing:
11.375 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:	6.500 i	inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:	Shaft Center To Mounting Surface Distance:	
	11.375	5 inches single end
10.750 inches	Cente	r To Center Distance Between Mounting Facilities Parallel To Length:
	10.750) inches

NSN 6105-00-500-1239

Direct Current Motor - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To Width:	
15.500 inches	
Current Rating In Amps:	
73.000 single input	
Connection Type And Voltage Rating In Volts:	
230.0 line to neutral single input	
Shaft End Characteristic:	
A9 single style single end	
Shelf Life:	

Demilitarization:

Unit Of Measure:

No

N/a

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.