NSN 6105-00-500-1239

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-500-1239

Overall Height:
25.500 inches
Overall Length:
31.500 inches
Overall Width:
25.562 inches
Keyway Width:
0.3750 inches single end
Keyway Depth:
0.5000 inches single end
Shaft Diameter:
2.0000 inches single end
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Dripproof-15 deg
Winding Type:
Compound wound
Mounting Method:
Fixed base
Ned base Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 unthreaded hole
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method:
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification:
Mounting Facility Type And Quantity:4 unthreaded holeCooling Method:Self-ventilatedCurrent Rating Method:LoadInclosure Specificationification:Mil-std-108
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Self-ventilated Current Rating Method: Load Inclosure Specificationification: Mil-std-108 Features Provided:
Mounting Facility Type And Quantity:4 unthreaded holeCooling Method:Self-ventilatedCurrent Rating Method:LoadInclosure Specificationification:Mil-std-108Features Provided:Vertical mounting position
Mounting Facility Type And Quantity:4 unthreaded holeCooling Method:Self-ventilatedCurrent Rating Method:LoadInclosure Specificationification:Mil-std-108Features Provided:Vertical mounting positionPower Rating:
Mounting Facility Type And Quantity:4 unthreaded holeCooling Method:Self-ventilatedCurrent Rating Method:LoadInclosure Specificationification:Mil-std-108Features Provided:Vertical mounting positionPower Rating:20.0000 horsepower output
Mounting Facility Type And Quantity:4 unthreaded hole4 unthreaded holeCooling Method:Self-ventilatedCurrent Rating Method:LoadInclosure Specificationification:Mil-std-108Features Provided:Vertical mounting positionPower Rating:20.0000 horsepower outputLength Of Shaft From Housing:
Mounting Facility Type And Quantity:4 unthreaded holeCooling Method:Self-ventilatedCurrent Rating Method:LoadInclosure Specificationification:Mil-std-108Features Provided:Vertical mounting positionPower Rating:20.0000 horsepower outputLength Of Shaft From Housing:6.500 inches single end
Mounting Facility Type And Quantity:4 unthreaded holeCooling Method:Self-ventilatedCurrent Rating Method:LoadInclosure Specificationification:Mil-std-108Features Provided:Vertical mounting positionPower Rating:20.0000 horsepower outputLength Of Shaft From Housing:6.500 inches single endShaft Center To Mounting Surface Distance:
Mounting Facility Type And Quantity:4 unthreaded hole4 unthreaded holeCooling Method:Self-ventilatedCurrent Rating Method:LoadInclosure Specificationification:Mil-std-108Features Provided:Vertical mounting positionPower Rating:20.0000 horsepower outputLength Of Shaft From Housing:6.500 inches single endShaft Center To Mounting Surface Distance:11.375 inches single end

40.0 ambient degrees celsius and 50.0 operating degrees celsius

NSN 6105-00-500-1239

Direct Current Motor - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To Width:

15.500 inches

Current Rating In Amps:

73.000 single input

Connection Type And Voltage Rating In Volts:

230.0 line to neutral single input

Shaft End Characteristic:

A9 single style single end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No Fiig: A271a0 Mil-std (military Standard): Mil-std-108 spec.