NSN 6105-00-500-1281

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-500-1281

| ····· -······························· | |
|---|--|
| Overall Height: | |
| 24.625 inches | |
| Overall Length: | |
| 35.875 inches | |
| Overall Width: | |
| 25.750 inches | |
| Keyway Width: | |
| 0.5000 inches single end | |
| Keyway Depth: | |
| 0.3750 inches single end | |
| Shaft Diameter: | |
| 2.1250 inches single end | |
| Keyway Length: | |
| 5.3750 inches single end | |
| Shaft Rotation Direction: | |
| Clockwise single end or counterclockwise single end | |
| Duty Cycle: | |
| Continuous | |
| Inclosure Feature: | |
| Dripproof-15 deg | |
| Winding Type: | |
| Compound wound | |
| Mounting Method: | |
| Fixed base | |
| Mounting Facility Type And Quantity: | |
| 4 unthreaded hole | |
| Cooling Method: | |
| Self-ventilated | |
| Current Rating Method: | |
| Load | |
| Inclosure Specificationification: | |
| Mil-std-108 | |
| Features Provided: | |
| Vertical mounting position | |
| Power Rating: | |
| 30.0000 horsepower output | |
| Length Of Shaft From Housing: | |
| 6.625 inches single end | |
| Shaft Center To Mounting Surface Distance: | |
| 11.000 inches single end | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 13.500 inches | |

NSN 6105-00-500-1281

Direct Current Motor - Page 2 of 2



Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm: 1750.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 17.500 inches **Current Rating In Amps:** 111.000 single input **Connection Type And Voltage Rating In Volts:** 230.0 line to neutral single input Shaft End Characteristic: A9 single style single end Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A271a0 Mil-std (military Standard): Mil-std-108 spec.