## NSN 6105-00-500-1388

Direct Current Motor - Page 1 of 2

Overall Height: 23.312 inches
Overall Width:



View Online at https://aerobasegroup.com/nsn/6105-00-500-1388

17.875 inches
Thread Length:
0.250 inches first end
Taper Length:
3.062 inches first end
Keyway Width:
0.312 inches first end
Keyway Depth:
0.156 inches first end
Shaft Diameter:
1.7500 inches first end
Keyway Length:
1.375 inches first end
Duty Cycle:
Intermittent
Inclosure Feature:
Dripproof-15 deg
Winding Type:
Compound wound
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Time Interval:
1.0 hours on
Cooling Method:
Self-ventilated
Current Rating Method:
Load
Inclosure Specificationification:
Inclosure Specificationification: Mil-std-108
•
Mil-std-108
Mil-std-108  Features Provided:
Mil-std-108  Features Provided:  Vertical mounting position
Mil-std-108  Features Provided:  Vertical mounting position  Frame Size Designation:
Mil-std-108  Features Provided:  Vertical mounting position  Frame Size Designation:  75
Mil-std-108  Features Provided:  Vertical mounting position  Frame Size Designation:  75  Power Rating:

## NSN 6105-00-500-1388

Direct Current Motor - Page 2 of 2



## **Shaft Center To Mounting Surface Distance:** 9.250 inches single end **Center To Center Distance Between Mounting Facilities Parallel To Length:** 10.750 inches **Tempurature Rating:** 45.0 ambient degrees celsius and 40.0 operating degrees celsius **Rotor Speed Rating In Rpm:** 1800.0 single full load **Center To Center Distance Between Mounting Facilities Parallel To Width:** 14.250 inches **Current Rating In Amps:** 56.000 single input **Connection Type And Voltage Rating In Volts:** 230.0 line to neutral single input Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-std (military Standard): Mil-std-108 spec.

A271a0