NSN 6105-00-500-3820

Direct Current Motor - Page 1 of 2



-	0 0 0
View Online at https://aerobasegroup.com/nsn/6105-00-500-3820	
Overall Height:	
21.000 inches	
Overall Length:	
29.313 inches	
Overall Width:	
18.625 inches	
Thread Length:	
0.8125 inches single end	
Shaft Diameter:	
0.625 inches single end and 1.000 inches single end	
Shaft Rotation Direction:	
Clockwise single end or counterclockwise single end	
Duty Cycle:	
Continuous	
Inclosure Feature:	
Dripproof-15 deg	
Winding Type:	
Compound wound	
Mounting Method:	
Fixed base	
Mounting Facility Type And Quantity:	
4 unthreaded hole	
Cooling Method:	
Self-ventilated	
Current Rating Method:	
Load	
Inclosure Specificationification:	
Mil-std-108	
Features Provided:	
Vertical mounting position	
Thready Qty Per Inch (tpi):	
18 single end	
Power Rating:	
10.0000 horsepower output	
Thread Size:	
0.625 inches single end	
Length Of Shaft From Housing:	
1.875 inches single end	

Center To Center Distance Between Mounting Facilities Parallel To Length: 11.250 inches

8.250 inches single end

Shaft Center To Mounting Surface Distance:

NSN 6105-00-500-3820

Direct Current Motor - Page 2 of 2



_				_		
Т	am	niir	atu	ro R	'atin	M.
	CIII	pui	atu	C 11	latii	ıy.

40.0 ambient degrees celsius and 50.0 operating degrees celsius

Rotor Speed Rating In Rpm:

78.0 single full load

Center To Center Distance Between Mounting Facilities Parallel To Width:

13.125 inches

Current Rating In Amps:

78.000 single input

Connection Type And Voltage Rating In Volts:

115.0 line to neutral single input

Shaft End Characteristic:

A2 first style single end and a9 second style single end

Special Features:

Two additional mtg holes located 11.375 in. Fwd of centerlineof motor at drive end on 5.250 in. Centers

Thread Series Designator:

Unf single end

Terminal Type And Quantity:

6 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.